

MULTI BUTTON DOOR CAMERA

DRC-2UC



PRODUCT FUNCTION

- 2 button wide name plate
- Material: Aluminum • House call and talk

SPECIFICATION

Power source	DC12V/1A
Operation Temp.	-10°C~50°C
Wiring	4 wire
Minimum Illumination	0.1Lux (up to 300mm)
Lighting	Flush-mounted white LED (3pie) 2 EA
Camera view angle	Horizontal 75°, Vertical 55°
Camera angle adjusting	Ascendant: 13° Descendant: 13°
Scanning frequency	NTSC/PAL
Distance	28m (0.5Ø) / 50m (0.65Ø)
Image Sensor	C-MOS(1/4 inch)
Dimension(mm)	130(W)×250(H)×10(D)

MULTI BUTTON DOOR CAMERA

DRC-3UC



PRODUCT FUNCTION

- 3 button wide name plate
- Material: Aluminum • House call and talk

SPECIFICATION

Power source	DC12V/1A
Operation Temp.	-10°C~50°C
Wiring	4 wire
Minimum Illumination	0.1Lux (up to 300mm)
Lighting	Flush-mounted white LED (3pie) 2 EA
Camera view angle	Horizontal 75°, Vertical 55°
Camera angle adjusting	Ascendant: 13° Descendant: 13°
Scanning frequency	NTSC/PAL
Distance	28m (0.5Ø) / 50m (0.65Ø)
Image Sensor	C-MOS(1/4 inch)
Dimension(mm)	130(W)×250(H)×10(D)

MULTI BUTTON DOOR CAMERA

DRC-4UC



PRODUCT FUNCTION

- 4 button wide name plate
- Material: Aluminum • House call and talk

SPECIFICATION

Power source	DC12V/1A
Operation Temp.	-10°C~50°C
Wiring	4 wire
Minimum Illumination	0.1Lux (up to 300mm)
Lighting	Flush-mounted white LED (3pie) 2 EA
Camera view angle	Horizontal 75°, Vertical 55°
Camera angle adjusting	Ascendant: 13° Descendant: 13°
Scanning frequency	NTSC/PAL
Distance	28m (0.5Ø) / 50m (0.65Ø)
Image Sensor	C-MOS(1/4 inch)
Dimension(mm)	130(W)×250(H)×10(D)

MULTI BUTTON DOOR CAMERA

DRC-5UC



PRODUCT FUNCTION

- 5 button wide name plate
- Material: Aluminum • House call and talk

SPECIFICATION

Power source	DC12V/1A
Operation Temp.	-10°C~50°C
Wiring	4 wire
Minimum Illumination	0.1Lux (up to 300mm)
Lighting	Flush-mounted white LED (3pie) 2 EA
Camera view angle	Horizontal 75°, Vertical 55°
Camera angle adjusting	Ascendant: 13° Descendant: 13°
Scanning frequency	NTSC/PAL
Distance	28m (0.5Ø) / 50m (0.65Ø)
Image Sensor	C-MOS(1/4 inch)
Dimension(mm)	130(W)×315(H)×10(D)

MULTI BUTTON DOOR CAMERA

DRC-6UC



PRODUCT FUNCTION

- 6 button wide name plate
- Material: Aluminum • House call and talk

SPECIFICATION

Power source	DC12V/1A
Operation Temp.	-10°C~50°C
Wiring	4 wire
Minimum Illumination	0.1Lux (up to 300mm)
Lighting	Flush-mounted white LED (3pie) 2 EA
Camera view angle	Horizontal 75°, Vertical 55°
Camera angle adjusting	Ascendant: 13° Descendant: 13°
Scanning frequency	NTSC/PAL
Distance	28m (0.5Ø) / 50m (0.65Ø)
Image Sensor	C-MOS(1/4 inch)
Dimension(mm)	130(W)×315(H)×10(D)

MULTI BUTTON DOOR CAMERA

DRC-7UC



PRODUCT FUNCTION

- 7 button wide name plate
- Material: Aluminum • House call and talk

SPECIFICATION

Power source	DC12V/1A
Operation Temp.	-10°C~50°C
Wiring	4 wire
Minimum Illumination	0.1Lux (up to 300mm)
Lighting	Flush-mounted white LED (3pie) 2 EA
Camera view angle	Horizontal 75°, Vertical 55°
Camera angle adjusting	Ascendant: 13° Descendant: 13°
Scanning frequency	NTSC/PAL
Distance	28m (0.5Ø) / 50m (0.65Ø)
Image Sensor	C-MOS(1/4 inch)
Dimension(mm)	130(W)×315(H)×10(D)