

Touch Series

Call Point Standard

L922



Features

- Large Call and Reset Buttons with tactical feedback for easy operation.
- Bright Multicoloured Re-assurance LED indicating call point status.
- NFC Reader to identify staff member using their Care-Card.
- Programmable Sounder for patient confirmation and call following.
- Pendant/Wrist wireless RF receiver built into the Call Point.
- Pear Lead Socket which supports Intercall range of wired devices.
- Backlit LCD Display Call Follower and status indication.
- Fully programmable to suit local requirements.

Overview

The L922 Call Point Standard is designed to be located near to the bed to allow Access by the staff and patient.

A Pear Lead may be inserted and operated by the patient to generate a call to the care staff. A Pear Removed alarm is generated should the Pear Lead be removed.

A large call button make activation easy and the unit is reset by staff using either their NFC Care Card or by using the Reset button.

The staff may register their attendance by use of their NFC Carecard or by the use of the Reset button.

Emergency or Crash calls may be generated by pressing the Call and Reset button simultaneously.

The integral multicoloured re-assurance LED clearly indicate the current event using a series of colours and is programmable as required.

The integral sounder also aids re-assurance and may be programmed as required.

The programmable 16 character LCD Display identifies the current event and displays waiting Calls while the unit is in nurse presence mode, together with the call follower sounder.

The integral RF receiver allows the unit to be activated remotely from a wrist fob or pendant without the need for trailing wires.

The unit forms part of the Intercall Touch range of products and is styled to complement other products in the Intercall Touch range.

The Intercall Touch system is fully addressable and comprises a two core data bus which powers this device while also delivering synchronisation data from the Intercall Touch Controller.

Specification

System: Intercall Touch Bus.

Power: Bus Powered Nominal 12V

Connection: Pear Lead Rj10.

NFC Frequency: 13.56MHz

NFC Standard: ISO15693

RF Frequency: 868MHz Band

Terminals:

BUS (+/-)

X1 Contact Input (Programmable)

X2 Contact Input (Programmable)

X3 Contact Input (Programmable)

X4 Contact Input (Programmable)

X5 Contact Input (Programmable)

Fixing: Wall Mounted.

Material: ABS Mix.

Finish: High Gloss white.

Weight: 130g

Dimensions

