

DATA SHEET



Pull Cord Module (NUPC3-HE)

Features

- IP44 splash-proof making it suitable for use in toilet and shower areas
- An active module connecting to an active room bus via RJ-45 connectors
- Call activated by a 2m (6.5ft.) long pull cord with a breakaway barrel
- Red LED call indicator above pull cord for call assurance
- System supports up to eight pull cord modules on the same room bus
- Optional blank button insert included with module

Technical Specifications

NUPC3–HE Overview

Item	NUPC3-HE: white (NCS S0300–N)
Material	
Material	PBT/PC enclosure rated UL94-V0
Color	Housing: White (NCS S0300–N)
	Button colors: Red: (NCS S1085-Y80R) Yellow: (NCS S0560-Y) Green: (NCS S2060-G)
Dimensions (H x W x D)	81 x 81 x 39 mm (3.19 x 3.19 x 1.54 in) with frame
Weight	167g (5.0 oz.)
Mounting	EU box (or equivalent) Single backbox with mounting holes 60mm (2.36in.) United Kingdom MK Honeywell models (or equivalent) 1-gang: 861ZIC, 866ZIC, 877ZIC Note: UK backboxes require a single (NUMP86-HK) mounting plate.
Pull cord	1x plastic covered nylon cord (breakaway barrel will limit pull force to 80N) Length 2.0m (6.5ft.)
Electrical	
Electrical rating	Input: 5.5VDC Current consumption: Idle: 5mA Max: 25mA
Wire type	Cat 5/5e/6/7, U/UTP Note: Cat 6/7 cable will work electrically but may be too stiff for some back boxes.
Electrical connections	2x RJ-45 (daisy chain) sockets for room bus

Specifications are subject to change without notice

Compatibility

Software Compatibility	Telligence 5.0 or higher teleCARE IP 13.0 or higher
------------------------	--

Hardware Compatibility	NUDL-series dome lights NIRC4 room controller NICL4 corridor lamps NURGW-H room gateway
------------------------	--

Environmental

Operating temperature:	0°C to 50°C (32°F to 122°F)
------------------------	-----------------------------

Storage temperature:	-25°C to 55°C (-13°F to 131°F)
----------------------	--------------------------------

Relative Humidity:	30 to 95% (non condensing)
--------------------	----------------------------

Enclosure protection rating:	IP44
------------------------------	------

Regulatory Compliance EU/EFTA

In conformity with the following EU directives and harmonized standards (the valid references are stated in the Declaration of Conformity):
EN 62368-1, EN 55035 (CISPR35), EN 55032 (CISPR32)
Class B, VDE 0834

Regulatory Compliance UK

In conformity with the following UK regulation and designated standards:
Radio Equipment Regulations 2017
The Restriction of the Use of Certain Hazardous Substances in Electrical and Electronic Equipment Regulations 2012
HTM 08-03
EN 55032
EN 55035
EN 62368-1

Regulatory Compliance ANZ

EN 55032

Specifications are subject to change without notice

Accessories

Accessories

Button Insert Kit EU (P/N NUCBK-HE)

Button Insert Kit UK (P/N NUCBK-HK)

Replacement pull-cord (P/N 660098)

Specifications are subject to change without notice

Ascom (Sweden) AB

Grimbodalen 2

SE-417 49 Göteborg

Sweden

Phone +46 31 55 93 00

www.ascom.com

ascom