

UniFi UISP Branding

Q

Search UniFi products

; Switching WiFi Camera Security Door Access Integrations Advanced Hosting



Standard > [Standard 48](#)

Datasheet

In The Box

Marketing Images

Installation Guide



^ Overview

Dimensions

442 x 285 x 44 mm
(17.4 x 11.2 x 1.7")

Port Layout

1 GbE RJ45

48
(1G/100M/10M)

1G SFP

4
(1G)

Form Factor

Rack mount (1U)

^ Performance

Switching Capacity

104 Gbps

Total Non-Blocking Throughput

52 Gbps

Forwarding Rate

77 Mpps

Supported VLANs	1,000
MAC Address Table Size	16,000
Packet Buffer Size	1.5 MB
Access Lists	
IPv4	128
MAC	128

^ Layer 2 Features

LACP Port Aggregation	✓
STP & RSTP	✓
Advanced IGMP Configuration (Querier, Fast Leave, Router Port)	✓
IGMP Snooping	✓
802.1X Control	✓
MAC-Based ACLs & Device Isolation	✓
DHCP Snooping & Guarding	✓
Egress Rate Limit	✓
Flow Control	✓
Storm Control	✓
Multicast & Broadcast Rate Limiting	✓
MAC Address Blocking	✓
IP-Based ACLs & Network Isolation	✓
MAC-Based Port Restriction	✓
Port Isolation	✓
Port Mirroring	✓
Jumbo Frames	✓
LLDP-MED	✓
Voice VLAN	✓

Loop Protection	✓
-----------------	---

^ Hardware

Max. Power Consumption	40W
------------------------	-----

Power Method	Universal input, 100—240V AC, 50/60 Hz
--------------	--

Power Input Method	AC input
--------------------	----------

Power Supply	AC/DC, internal, 60W
--------------	----------------------

Supported Voltage Range	100—240V AC
-------------------------	-------------

Management	Ethernet AR
------------	----------------

Heat Dissipation (Excluding PoE Output)	136.48 BTU/hr
---	---------------

Weight	Without mounting brackets: 3.9 kg (8.6 lb) With mounting brackets: 4 kg (8.8 lb)
--------	---

Enclosure Material	SGCC steel
--------------------	------------

Mount Material	SGCC steel
----------------	------------

Supported Rack Depth	400~1200 mm (15.7-47.2")
----------------------	-----------------------------

LCM Display	1.3" touchscreen
-------------	------------------

Ambient Operating Temperature	-15 to 40° C (5 to 104° F)
-------------------------------	----------------------------

Ambient Operating Humidity	10 to 90% noncondensing
----------------------------	-------------------------

NDAA Compliant	✓
----------------	---

Certifications	CE, FCC, IC, Anatel
----------------	---------------------

^ Software

Application Requirements	
--------------------------	--

UniFi Network	Version 7.2.94 and later
---------------	--------------------------