

ITME: VD-03A



Specification:

Product name : **12V DC 03 Amp 04 channel CCTV Power Supply**

Item : **ATP1203-04C (VD-03A)**

Details :

Use of efficient, environmental protection switching power supply circuit frame

Optimization of the shape and structure to facilitate the construction systems

Small ripple & noise -- video output signal more stable, clearly images

Shunt output -- by-pass failure to protect other equipment to work

Power protection -- Output over-voltage protection, over-current protection, short circuit protection

Input: 100-240V AC @ 50-60Hz

Output voltage: 11-14V DC ADJ

Output volt-regulation Precision: 12-14V DC ADJ

Output Current: 3Amp

Output Channel: 4 Channel

Overcurrent Protection: 4A±5%

Ripple & Noise: ≤50mV

Efficiency ≥85%

Metal box color: Gray

Output fuse type: Glass fuse

Triple electronic protection: Short circuit, Overload, surge

Enclosure Dimensions: 163*163*48mm

Weight: 0.76kg



Specification:

Product name : **12V DC 10 Amp 09Way CCTV Power Supply in Metal Enclosure**

Item : ATP1210-09C (VD-10A)

Details :

Metal box with key lock

Individual LED indicators and fuse for each output

Triple electrical protection

Adjustable Output Voltage

Product Type: Switching Power Supply

Mains Input:100-240V AC @ 50/60Hz

Output voltage: 11-14V DC ADJ

Output Current: 10Amp

Output Channel: 9 Channel

Overcurrent Protection: 11A±5%

Ripple & Noise: ≤50mV

Efficiency ≥85%

Number of output: 9Way

Output fuse type: PTC Self reset able fuse

Triple electronic protection: Short circuit, Overload, surge

Metal box color: Gray

Enclosure Dimensions: 200*203*50mm

Weight: 1.4kg



Specification:

Product name : **12V DC 16Amp 16Way CCTV Power Supply in Metal Enclosure**

Item : ATP1216-16C (VD-16A)

Details :

Metal box with key lock

Individual LED indicators and fuse for each output

Triple electrical protection

Adjustable Output Voltage

Product Type: Switching Power Supply

Mains Input:110VAC/220V AC @ 50/60Hz

Output voltage: 12-14V DC ADJ

Output Current: 16Amp

Output Channel: 16Channel

Overcurrent Protection: 17A±5%

Ripple & Noise: ≤50Mv+

Efficiency ≥85%

Number of output: 16Way

Output fuse type: Glass fuse

Triple electronic protection: Short circuit, Overload, surge

Metal box color: Gray

Enclosure Dimensions: 342*186*55mm

Weight: 2.1kg